Proof-Theoretic Interconnections between Known Inference- and Axiom-Systems for Recursive Type Equality

Clemens Grabmayer

clemens@cs.vu.nl
www.cs.vu.nl/~clemens

Theoretical Computer Science group,
Vrije Universiteit Amsterdam

My Supervisors:

Jan Willem Klop,
Roel de Vrijer

Type: A collection of values sharing a common shape or structure,

e.g. basic types: **Unit**, **Int**, **Float**

structured types: $\mathbf{Int} \to \mathbf{Int}$, $\mathbf{Int} \times \mathbf{Int}$, $\mathbf{Unit} + \mathbf{Int}$,

where $\mathbf{Unit} := \{\text{val}\}$.

Recursive Type: A type, that satisfies a *recursive type equation* like

$\mathbf{Tree} = \mathbf{Int} + (\mathbf{Tree} \times \mathbf{Tree})$ type of binary trees with integer leaves

$\mathbf{A_List} = \mathbf{Unit} + (\mathbf{A} \times \mathbf{A_List})$ type of lists with members of type $\mathbf{A}$.

For recursive type equations like

$$\tau = \mathbf{Unit} + (\mathbf{A} \times \tau) \tag{1}$$

in theoretical contexts often *canonical solutions* in the form of a μ-expression

$$\mu\alpha.\,(\mathbf{Unit} + (\mathbf{A} \times \alpha)) \quad =:\ \sigma$$

are considered. Assuming the presence of a conversion

$$\mu\beta.\,\rho = \rho[\mu\beta.\,\rho/\beta] \ \ (\text{FOLD/UNFOLD})$$

the μ-type σ can then be seen to satisfy equation (1) for τ:

$$\begin{aligned}\sigma = \mu\alpha.\,(\mathbf{Unit} + (\mathbf{A} \times \alpha)) &= (\mathbf{Unit} + (\mathbf{A} \times \alpha))\,[\sigma/\alpha] \\ &= \mathbf{Unit} + (\mathbf{A} \times \sigma) \ .\end{aligned}$$

There is also an intuitive need for identifying such solutions of recursive type equations that solve a common equation. E.g. in the case of the equations

$$\tau = \mathbf{Unit} + (\mathbf{A} \times \tau) \tag{2}$$

and

$$\tau = \mathbf{Unit} + (\mathbf{A} \times (\mathbf{Unit} + \mathbf{A} \times \tau)) \tag{3}$$

every solution to (2) also solves (3). – And intuitively they possess the same solution

$$\mathbf{A_List} := \{\mathrm{val}, (a_0, \mathrm{val})), (a_0, (a_1, \mathrm{val})), \ldots : a_0, a_1, \ldots \in A\}$$

(if $\mathbf{Unit} = \{\mathrm{val}\}$).

Therefore also

$$\begin{aligned} &\mu\alpha.\,(\mathbf{Unit} + (\mathbf{A} \times \alpha)) = \\ &\qquad = \mu\alpha.\,(\mathbf{Unit} + (\mathbf{A} \times (\mathbf{Unit} + \mathbf{A} \times \alpha))) \end{aligned}$$

should hold. This means that canonical solutions that satisfy the same equation

$$\alpha = \tau(\alpha)$$

can—under certain restrictions on τ and α—be identified. In a formal system this leads to a rule

$$\frac{\tau_1 = \tau[\tau_1/\alpha] \qquad \tau_2 = \tau[\tau_2/\alpha]}{\tau_1 = \tau_2}\ \mathrm{UFP} \quad .$$

Recursive Types

Recursive Types μTp:

$$\tau ::= \alpha \,|\, \bot \,|\, \top \,|\, \tau_1 \to \tau_2 \,|\, \mu\alpha.\, \tau_0 \qquad (\alpha \in TVar).$$

Recursive Types in canonical form can-μTp:

$$\tau ::= \alpha \,|\, \bot \,|\, \top \,|\, \tau_1 \to \tau_2 \,|\, \mu\alpha.\underbrace{\tau_1 \to \tau_2}_{\text{where } \alpha \in \mathrm{fv}(\tau_1 \to \tau_2)} \qquad (\alpha \in TVar).$$

Definition 1. (Recursive Type Equality $=_\mu$ (Strong Recursive Type Equivalence))

For all $\tau, \sigma \in \mu Tp$:

$$\tau =_\mu \sigma \;:\Longleftrightarrow\; \mathbf{Tree}(\tau) = \mathbf{Tree}(\sigma)\,.$$

$\boxtimes$

Definition 2. (**Tree-Unfolding of Recursive Types in canonical Form**)

The function **Tree**

$$\mathbf{Tree}: \text{ can-}\mu Tp \longrightarrow \text{Labelled Binary Trees}$$
$$\tau \longmapsto \mathbf{Tree}(\tau)$$

which describes the *tree-unfolding* of recursive types in canonical form is defined by:

$\mathbf{Tree}(\bot) :=$; $\mathbf{Tree}(\top) :=$; $\mathbf{Tree}(\alpha) :=$;

$\mathbf{Tree}(\tau_1 \to \tau_2) :=$ 

;

$\mathbf{Tree}(\underbrace{\mu\alpha.\,(\tau_1 \to \tau_2)}_{\equiv:\tau}) :=$ 

.

⊠

Example 1 (Tree-Unfolding).

The recursive type

$$\tau := \mu\alpha.\,(\bot \to \alpha)$$

corresponds to the *cyclic term-graph*



and has the tree-unfolding

Tree(τ)=



■

Example 2 (Tree-Unfolding).

The recursive types

$$\tau := \mu\alpha.\,((\alpha \to \alpha) \to \alpha) \qquad \text{and}$$
$$\sigma := \mu\alpha.\,(\alpha \to (\alpha \to \alpha))$$

correspond respectively to the different cyclic term-graphs



and



but possess the same tree-unfolding

Tree(τ)=**Tree**(σ)=



and hence $\tau =_\mu \sigma$ holds, i.e. recursive type equality holds between τ and σ.

■

Definition 3. (The axiom-system $\mathbf{AC}^{=}$ for recursive type equality $=_\mu$)

Axioms:

(REFL) $\overline{\tau = \tau}$ (VAR) $\overline{\tau = \tau'}$ (if $\tau \equiv_{\mathrm{v}} \tau'$)

$(\mu - \bot)$ $\overline{\mu\alpha.\,\alpha = \bot}$ (FOLD/UNFOLD) $\overline{\mu\alpha.\,\tau = \tau[\mu\alpha.\,\tau/\alpha]}$

Rules:

$$\frac{\sigma = \tau}{\tau = \sigma}\ \text{SYMM} \qquad \frac{\tau_1 = \sigma_1 \qquad \tau_2 = \sigma_2}{\tau_1 \to \tau_2 = \sigma_1 \to \sigma_2}\ \text{ARROW}$$

$$\frac{\tau = \sigma}{\mu\alpha.\,\tau = \mu\alpha.\,\sigma}\ \mu\text{-COMPAT} \qquad \frac{\tau = \rho \qquad \rho = \sigma}{\tau = \sigma}\ \text{TRANS}$$

$$\frac{\tau_1 = \tau[\tau_1/\alpha] \qquad \tau_2 = \tau[\tau_2/\alpha]}{\tau_1 = \tau_2}\ \text{UFP} \quad (\text{if } \alpha \downarrow \tau)$$

(where $\alpha \downarrow \tau$ means that τ is *contractive* w.r.t. α). ⊠

Theorem 1 (R. Amadio, L. Cardelli, '93). *For all recursive types* $\tau, \sigma \in \mu Tp$: $\tau =_\mu \sigma \iff \vdash_{AC^=} \tau = \sigma$.

Definition 4. (The axiom-system $\mathbf{HB}^{=}$ for recursive type equality $=_\mu$)

Axioms:

Rules:

$$\frac{\begin{array}{cc}\langle \tau_1 \to \tau_2 = \sigma_1 \to \sigma_2 \rangle^x & \langle \tau_1 \to \tau_2 = \sigma_1 \to \sigma_2 \rangle^x \\ \mathcal{D}_1 & \mathcal{D}_2 \\ \tau_1 = \sigma_1 & \tau_2 = \sigma_2\end{array}}{\tau_1 \to \tau_2 = \sigma_1 \to \sigma_2}\ (\mathrm{ARROW/FIX})_x$$

$\boxtimes$

(REFL) $\overline{\tau = \tau}$ $(\mu - \bot)'$ $\overline{\mu\alpha\alpha_1 \ldots \alpha_n . \alpha = \bot}$

(VAR) $\overline{\tau = \tau'}$ (if $\tau \equiv_{\mathrm{v}} \tau'$) (FOLD/UNFOLD) $\overline{\mu\alpha . \tau = \tau[\mu\alpha . \tau/\alpha]}$

$$\frac{\sigma = \tau}{\tau = \sigma}\ \text{SYMM} \qquad \frac{\tau = \rho \qquad \rho = \sigma}{\tau = \sigma}\ \text{TRANS}$$

Theorem 2 (M. Brandt (and F. Henglein), '98).

For all recursive types $\tau, \sigma \in \mu Tp$:

$$\tau =_\mu \sigma \iff \vdash_{HB^=} \tau = \sigma\,.$$

Definition 5. (The syntactic-matching inference-system $\mathrm{SM}^{=}$ for checks concerning recursive type equality $=_\mu$)

Axioms:

$$\text{(REFL)}\ \frac{}{\tau = \tau} \qquad (\mu - \bot)'\ \frac{}{\mu\alpha\alpha_1 \ldots \alpha_n.\, \alpha = \bot}$$

$$\text{(VAR)}\ \frac{}{\tau = \tau'}\ (\text{if } \tau \equiv_{\mathrm{v}} \tau') \qquad \text{(FOLD/UNFOLD)}\ \frac{}{\mu\alpha.\, \tau = \tau[\mu\alpha.\, \tau/\alpha]}$$

Rules:

$$\frac{\sigma = \tau}{\tau = \sigma}\ \text{SYMM} \qquad \frac{\tau = \rho \qquad \rho = \sigma}{\tau = \sigma}\ \text{TRANS}$$

$$\frac{\tau_1 \to \tau_2 = \sigma_1 \to \sigma_2}{\tau_i = \sigma_i}\ \text{DECOMP}\quad (i = 1, 2)$$

⊠

Definition 6. For all recursive types $\tau, \sigma \in \mu Tp$:

$\tau = \sigma$ is *$SM^{=}$-consistent* : $\iff$

$\iff$ For all $\chi_1, \chi_2 \in \mu Tp$:

$$\tau = \sigma \vdash_{\mathrm{SM}^{=}} \chi_1 = \chi_2 \implies \mathcal{L}(\chi_1) \equiv \mathcal{L}(\chi_2)\,.$$

Hereby for all $\tilde{\tau} \in \mu Tp$ the notation $\mathcal{L}(\tilde{\tau})$ designates the *leading symbol* of $\tilde{\tau}$. ⊠

Theorem 3 ((∼) Z.M. Ariola, J.W. Klop, 1995). *For all recursive types $\tau, \sigma \in \mu Tp$:*

$$\tau =_\mu \sigma \iff \tau = \sigma \text{ is } SM^{=}\text{-consistent}.$$

Definition 7 (Leading Symbol of a Recursive Type). For every recursive type $\tau \in \mu Tp$ its *leading symbol* $\mathcal{L}(\tau)$ is formally defined by induction on τ:

$$\mathcal{L}(\bot) :\equiv \bot\,,\ \mathcal{L}(\top) :\equiv \top$$
$$\mathcal{L}(\alpha) :\equiv \alpha \quad (\text{for } \alpha \in \mu Tp)$$
$$\mathcal{L}(\tau_1 \to \tau_2) :\equiv \to$$
$$\mathcal{L}(\mu\alpha_1 \ldots \alpha_n.\, \alpha) :\equiv \alpha \quad (\text{if } \alpha \not\equiv \alpha_i \text{ for } 1 \leq i \leq n)$$
$$\mathcal{L}(\mu\alpha_1 \ldots \alpha_n.\, \alpha_i) :\equiv \bot \quad (\text{for } 1 \leq i \leq n)$$
$$\mathcal{L}(\mu\alpha_1 \ldots \alpha_n.\, (\rho_1 \to \rho_2)) :\equiv \to \quad .$$

$\boxtimes$

Definition 8. (The axiom-system $\mathbf{HB}_0^{=}$ for recursive type equality $=_\mu$)

Axioms: $\overline{\tau = \tau}$ (REFL)

Rules:

$$\frac{\tau = \sigma}{\tau' = \sigma'} \text{ VAR} \qquad \frac{\bot = \sigma}{\mu\alpha_1\alpha_2 \ldots \alpha_n.\, \alpha_1 = \sigma} \; (\mu - \bot)_{\mathrm{l}}^{\mathrm{inf}} + (\mu - \bot)_{\mathrm{r}}^{\mathrm{inf}}$$

$$\frac{\tau_0[\mu\alpha.\, \tau_0/\alpha] = \sigma}{\mu\alpha.\, \tau_0 = \sigma} \text{ FOLD}_{\mathrm{l}} \qquad \frac{\tau = \sigma_0[\mu\alpha.\, \sigma_0/\alpha]}{\tau = \mu\alpha.\, \sigma_0} \text{ FOLD}_{\mathrm{r}}$$

$$\frac{\begin{array}{cc} \langle \tau_1 \to \tau_2 = \sigma_1 \to \sigma_2 \rangle^x & \langle \tau_1 \to \tau_2 = \sigma_1 \to \sigma_2 \rangle^x \\ \mathcal{D}_1 & \mathcal{D}_2 \\ \tau_1 = \sigma_1 & \tau_2 = \sigma_2 \end{array}}{\tau_1 \to \tau_2 = \sigma_1 \to \sigma_2} \; (\text{ARROW/FIX})_x$$

$\boxtimes$

Definition 9. (The axiom-system $\mathbf{SM}_0^{=}$ for recursive type equality $=_\mu$)

Rules:

$$\frac{\tau = \sigma}{\tau' = \sigma'} \text{ VAR} \qquad \frac{\mu\alpha_1\alpha_2 \ldots \alpha_n.\, \alpha_1 = \sigma}{\bot = \sigma} \; (\mu - \bot)_{\mathrm{l}}^{\mathrm{der}} + (\mu - \bot)_{\mathrm{r}}^{\mathrm{der}}$$

$$\frac{\mu\alpha.\, \tau_0 = \sigma}{\tau_0[\mu\alpha.\, \tau_0/\alpha] = \sigma} \text{ UNFOLD}_{\mathrm{l}} \qquad \frac{\tau = \mu\alpha.\, \sigma_0}{\tau = \sigma_0[\mu\alpha.\, \sigma_0/\alpha]} \text{ UNFOLD}_{\mathrm{r}}$$

$$\frac{\tau_1 \to \tau_2 = \sigma_1 \to \sigma_2}{\tau_i = \sigma_i} \text{ DECOMP} \quad (i = 1, 2)$$

$\boxtimes$

Example 3 ("Consistency Check" in $\mathbf{SM}_0^{=}$).

$$\dfrac{\dfrac{\dfrac{

Example 4 (Proof in $\mathrm{HB}_0^{=}$).

$$\dfrac{\dfrac{\dfrac{\dfrac{\dfrac{(\dots)^{y}}{\tau=\sigma}\quad\dfrac{\dfrac{(\dots)^{x}}{\tau\to\tau=\sigma}\quad\dfrac{(\dots)^{y}}{\tau=\sigma}}{(\tau\to\tau)\to\tau=\sigma\to\sigma}}{\tau=\sigma\to\sigma}\,\mathrm{x}}{\tau\to\tau=\sigma\to(\sigma\to\sigma)}}{\tau\to\tau=\sigma}\qquad\dfrac{\dfrac{\dfrac{\dfrac{(\dots)^{y}}{\tau=\sigma}\quad\dfrac{(\dots)^{z}}{\tau=\sigma\to\sigma}}{\tau\to\tau=\sigma\to(\sigma\to\sigma)}\quad\dfrac{(\dots)^{y}}{\tau=\sigma}}{\tau\to\tau=\sigma}\,\mathrm{z}}{(\tau\to\tau)\to\tau=\sigma\to\sigma}}{\tau=\sigma\to\sigma}\,\mathrm{y}$$

$$\dfrac{(\tau\to\tau)\to\tau=\sigma\to(\sigma\to\sigma)}{\underbrace{\mu\alpha.\,((\alpha\to\alpha)\to\alpha)}_{\equiv:\,\tau}=\underbrace{\mu\alpha.\,(\alpha\to(\alpha\to\alpha))}_{\equiv:\,\sigma}}$$

■

"Results"

1. There is an immediate "duality" between "consistency checks" in $\mathrm{SM}_0^=$ and derivations in $\mathrm{HB}_0^=$ (*Jan Willem Klop*).
2. μ-COMPAT is a derived rule of $\mathrm{AC}_1^=$.
3. An effective translation of $\mathrm{AC}^=$-derivations into $\mathrm{HB}^=$-derivations.
4. An effective translation of $\mathrm{HB}^=$- into $\mathrm{AC}^=$-derivations.
   a. A Transformation of $\mathrm{HB}^=$- into $\mathrm{HB}_0^=$-derivations.
   b. An effective translation of $\mathrm{HB}_0^=$- into $\mathrm{AC}^=$-derivations.

5. A "*Liberalisation*" e-HB$^{=}$ of HB$^{=}$ with rules such as

$$\dfrac{\begin{array}{c}[\tau = \mu\alpha.\,\sigma_0]^x \\ \mathcal{D} \\ \tau = \sigma_0[\mu\alpha.\,\sigma_0/\alpha]\end{array}}{\tau = \mu\alpha.\,\sigma_0}\ (\mathrm{FOLD/FIX})_x \quad (\mathcal{D} \text{ is } \textit{contractive})\ .$$

6. Transferring these results to the more general situation of analoguous proof-theoretic interconnections between formal systems AC$^{\leq}$, HB$^{\leq}$ and SM$^{\leq}$ for the *subtype-relation* between recursive types.

   Some further observations concerning details about the connections between derivations in these more general systems.

References

[AmCa93] Amadio, R.M., Cardelli, L.: "Subtyping Recursive Types", *ACM Transactions on Programming Languages and Systems 15 (4)*, pp. 575–631, 1993.

[ArKl95] Ariola, Z.H., Klop, J.W.: "Equational Term Graph Rewriting", *Fundamenta Informaticae 26 (3,4)*, pp. 207–240, June 1996; extended version as: *University of Oregon Technical Report CIS–TR–95–16*, 1995; and as: *Vrije Universiteit Amsterdam Technical Report IR–391*, September 1995.

[BrHe98] Brandt, M., Henglein, F.: "Coinductive Axiomatization of Recursive Type Equality and Subtyping", *Fundamenta Informaticae 33*, pp. 1–30, 1998.